



ABBREVIATIONS



| | |
|---------------------|-------------------------------|
| Prefab. S.A. | Prefabricated spring assembly |
| Approx. | Approximately |
| Ins.Ø | Inside diameter |
| 6P.C. | Hexagon socket |
| H.R. | High resistance |

MATERIAL

| | |
|-----------------|--------------------------------------|
| Alu | Aluminium |
| A.B.S. | Acrylonitrile Butadiene Styrene |
| ASA | Acrylonitrile Styrene Ester Acrylic |
| P.A. | Polyamide |
| P.A.F.V. | Polyamide reinforced with fibreglass |
| P.B.T. | Polybutylene terephthalate |
| P.O.M. | Polyoxymethylene or acetal resin |
| P.P. | Polypropylene |
| P.S. | Polystyrene |
| P.V.C. | Polychlorure de vinyle |
| P.S.Choc | Polystyrène choc |
| PE | Polyéthylène |

SCREW

| | |
|-------------|-----------------|
| H.R. | High resistance |
|-------------|-----------------|

SCREW

| | |
|---------------|-------------------------------------|
| CBL | Screw with cylindrical broad head |
| TFB | Raised countersunk head |
| TH | Hexagon head |
| TC | Cheese head |
| TF | Countersunk head |
| V.B.A. | Screw with pan head for flake board |
| CHC | Hexagon socket cylindrical head |
| Nut HU | Hexagon nut |

UNITS OF MEASUREMENT all the dimensions are given in millimeters, except indication

| | |
|-----------------------|---------------------------|
| mm | Millimeter |
| m or ml | Meter |
| µ | Thousands of millimeter |
| N | Newton meter |
| da N | Decanewton (approx. 1 kg) |
| m da N | Meter decanewton |
| Nm | Newton meter |
| cm⁴ | Unit of inertia moment |